

ENJOY THE PERFORMANCE AND EASY HANDLING



VERSATILE, IMPRESSIVE COST EFFECTIVENESS

Economical 12-Inch Continuous Laser Printer

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Compact design to fit in limited floor space
- Accurate media stacking, up to 2,000 pages
- S User-friendly, easy set-up, easy to operate
- > Tear-off edge for separating of printed form sets
- Replacement product for aging, end-of-life, SOLID F24, SOLID F32 or comparable printers!

FIELD OF APPLICATION

1

- > Oil and gas well logs, 1-up address label
- USPS required intelligent Mail Barcode (IMB)
- Banking, Insurance, Health services, Logistics, Distribution



SOLID F44



Print Engine

Print technology Controller Print speed

Print resolution Duty cycle

Power supply

Acoustic noise Dimensions (WxDxH)

Weight Environment temperature **Relative humidity** Interfaces:

Memory

LED, OPC, heat/pressure fixing Power PC 44 pages/minute (letter, landscape); 34 pages/minute (11" length) 2.267 lines/minute at 6 lines/inch 600 dpi x 600 dpi up to 50,000 pages/month (letter format)

100-110 V AC, 50 - 60 Hz / 12 Amps 110-120 V AC, 50 - 60 Hz / 11 Amps 220-240 V AC, 50 - 60 Hz / 6 Amps < 60 dB (A) operating 21.2" x 23.1" x 19.6" (inclusive tractor cassettes)

88.2 lbs including imaging cartridge 50 - 95 °F (operating), 32 - 95 °F (storage) 15 - 85 % (operating), 30 - 85 % (storage) Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP) IEEE 1284 (Centronics) ,RS232/RS422

RAM: 128 MB Flash: 32 MB

Power PC Print-Controller

Emulations

HP LaserJet 4 (PCL 5e, PJL), HP - GL/2, PCL/PJL Extensions (Optional data stream Converter available for IPDS)

Optional Emulations

Printronix IGP

Barcodes

USPS IMB and Postnet, Code 39, Code 93, Code 128, Codabar, 2/5 industrial, 2/5 interleaved, EAN 8/13 Add on 2/5, MSI, UPC-A, UPC-E, KIX-Code, Datamatrix Code

Optional Functions

iPS (intelligent Paper Stacker) F44: Assures accurate stacking of forms up to 2,000 pages, without ope-rator involvement

SPECIFICATIONS



Printable Media

Size	
Form length	3" - 20"
With stacker	7" - 17"
Form width	4" - 12"
Printable area	11"

Weight

17 - 42 lb (64 - 155 g/m²)

Paper Path

Input

From front with use of Tractor-feed Assembly

Output

Out top, directed to the rear with media guide

Optional

2,000 sheet stacker

The brand names referred to are the registered trademarks of the res-pective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 12.07.2022

MICROPLEX PRINTWARE AG Panzerstraße 5, 26316 Varel Germany Phone: +49 4451 91370 E-Mail: sales@microplex.de

USA

MICROPLEX PRINTWARE CORPORATION 30300 Solon Industrial Pkwy Suite E, Solon, OH 44139 Phone: +1 440-374-2424 E-Mail: info@microplex-usa.com

